



WHERE INNOVATION MEETS ILLUMINATION

+91-40-35825879

sales@srivintec.com

+91-9849521110

www.srivintec.com

Illumination That Inspires Innovation

Technical Specifications:

- 1.Power: 50W
- 2.Voltage range: 9-32V DC
- 3.Luminous flux: 4500LM
- 4.Light type: 5pcs 10W Osram LEDs
- 5.IP rating: IP69K
- 6.Material: PC lens, ADC12 aluminum alloy housing,4mm 304 stainless steel bracket
7. With breather filters
- 8.Operating temperature: -45°C+85°C
- 9.Beam: flood beam 80 degree
- 10.With built-in Deutsch connector
- 11.Bolt size: M10*25
12. Colour Temperature : 5300-5700K
- 14.Vibration: up to 60G



Model: SV-8100-50

Technical Specifications:

1. Power: 42W
2. Voltage range: 9-32V DC
3. Luminous flux: 3000LM
4. Light type: 14pcs 3W Bridgelux LEDS
5. IP rating: IP68
6. Material: PC lens, aluminum alloy housing,
7. 304 stainless steel bracket
8. Operating temperature: -45°C+85°C
9. Beam: flood beam 38°
- 10.With built-in Deutsch connector
- 11.Bolt size: M10*25
- 12.Colour Temperature : 5300- 5700K
- 13.Vibration Resistance: up to 30G



Model: SV-4141-30

Illumination That Inspires Innovation

Technical Specifications:

1. Power: 45W
2. Voltage range: 9-32V DC
3. Luminous flux: 3000LM
4. Light type: 15pcs 3W Bridgelux LEDS
5. IP rating: IP67
6. Material: PC lens, aluminum alloy housing,
7. 304 stainless steel bracket
8. Operating temperature: -45°C-+85°C
9. Beam: flood beam 80°
10. With open wire
11. Bolt size: M10*25
12. Colour Temperature : 6000K
13. Vibration Resistance: up to 20G



Model: SV-8145-45

Technical Specifications:

1. Power: 27W
2. Voltage range: 10-80V DC
3. Luminous flux: 1500LM
4. Light type: 9pcs 3W Bridgelux LEDS
5. IP rating: IP67
6. Material: PC lens, aluminum alloy housing,
7. 304 stainless steel bracket
8. Operating temperature: -45°C-+85°C
9. Beam: flood beam 40°
10. With open wire
11. Bolt size: M10*25
12. Colour Temperature : 6000K
13. Vibration Resistance: up to 20G



Model: SV-4145-27